



A. Unaltered 88 Monte Carlo Nose Piece and Tail piece only.

B. Minimum 4 inches from the ground (including skirting).

C. Minimum 107.5 inches both sides, maximum 1 inch difference from side to side.

D. OEM or fiberglass "G" body roofs only. Maximum 7 inch tall sun visor allowed.

E. B-Pillars may be trimmed to a minimum of two inches.

F. Stock appearing one piece, steel or aluminum hoods with air cleaner opening allowed.

G. Everything from the speaker deck to edge of tail piece must slope downhill towards rear of car.

H. Dash may be a maximum 36 inches from back of engine block.

I. Speaker deck may extend from drivers seat to back of "C" pillars or a maximum of 99 inches whichever comes first.

J. Minimum of three windshield bars must be in place in front of driver

K. Minimum height of 8 inches

L. Maximum downward slope from "A" pillar to nose of 2 inches.

M. Maximum length of 41 inches.

N. Maximum length of 27 inches, (not including skirting) same front to back. Minimum 3 inches of outward bow.

O. Maximum width of 66 inches at top of doors.

P. Maximum width of top of fender of three inches

Q. Minimum wheel opening of two inches larger than outside of tire and same on both sides of car.

R. Same measurement from left to right sides of quarter panels.

S. Maximum length of 48 inches

T. Minimum window opening of 16 inches in rear and 15 inches in front.

U. Minimum opera window dimension of 10" on top, 13" on bottom, 15" tall.

V. Standard 1988 Monte Carlo "C" pillar.

Fabricated Bodies must follow all dimensions of this body diagram.

O.E.M. Bodies must follow the underlined dimensions of this body diagram.